

# EDGE™ Housing 2 rack units, Gray, holds up to 24 EDGE modules or panels

CORNING

**Part Number:  
EDGE-02U**

EDGE™ housings are high-density, preterminated fibre optic hardware solutions. They offer industry-leading connector density and easy finger/toolless access to enable faster moves, adds, and changes (MACs). The units can be configured to accommodate 96, 144, 288, or 576 fibers.

EDGE housings can be rack- or cabinet-mounted and are ideal for data centers, local area network (LAN) and storage area network (SAN) applications, as well as enterprise networks.



# EDGE™ Housing 2 rack units, Gray, holds up to 24 EDGE modules or panels



EDGE™ Housing, 2 rack units, holds up to 24 EDGE modules or panels



EDGE™ Housing, 2 rack units, holds up to 24 EDGE modules or panels

## Specifications

General Specifications	
Product type	Housings
Access type	Front and rear access slidable
Mounting Type	Rack-mount, Cabinet-mount
Application	Data Centre, Enterprise Networks

Standards	
RoHS	Free of hazardous substances according to RoHS 2011/65/EU

Design	
Lockable	Yes
Number of modules	24
Cable entry type	Side brush entry
Number of Panels/Cassettes per Housing	24

# EDGE™ Housing 2 rack units, Gray, holds up to 24 EDGE modules or panels

CORNING

## Design

Cable Entry Direction	Rear
Housing type	EDGE™
Colour	Silver
Panel or cassette type	EDGE™
Panel or module type	EDGE™
Fibre Capacity	288

## Design - Adapter

Adapter housing colour	Silver
------------------------	--------

## Dimensions

Height	88 mm
Width	432 mm
Depth	561 mm
Weight	8.6 kg

## Ordering Information

Product Number	EDGE-02U-GND
Package contents	EDGE™ Housing 2U; Quick Start Guide, #12-24 and #10-32 mounting screws, Cage Nut Mounting Kit, Velcro Strap, Fiber Optic Warning Label
Shipping weight	10.9 kg
Module Capacity	24
Height Unit	2 U
Units per delivery	1/1
Trunk Capacity	24 (size 1 or 2, double stack cradle)
Shipping Height	216 mm
Shipping Width	565 mm

# EDGE™ Housing 2 rack units, Gray, holds up to 24 EDGE modules or panels



## Ordering Information

Shipping Depth

660 mm



Corning Optical Communications GmbH & Co. KG • Leipziger Strasse 121 • 10117 Berlin, Germany  
+00 800 2675 4641 • FAX: • [www.corning.com/opcomm/emea](http://www.corning.com/opcomm/emea)

A complete listing of the trademarks of Corning Optical Communications is available at [www.corning.com/opcomm/emea/trademarks](http://www.corning.com/opcomm/emea/trademarks). Corning Optical Communications is ISO 9001 and ISO 14001 certified. © 2025 Corning Optical Communications. All rights reserved.