

Part Number: EDGE-04U

EDGE™ housings are high-density, preterminated fibre optic hardware solutions. They offer industry-leading connector density and easy finger/toolless access to enable faster moves, adds, and changes (MACs). The units can be configured to accommodate 96, 144, 288, or 576 fibers.

EDGE housings can be rack- or cabinet-mounted and are ideal for data centers, local area network (LAN) and storage area network (SAN) applications, as well as enterprise networks.









Specifications

General Specifications	
Product type	Fibre Optic Hardware
Access type	Front and rear access slidable
Mounting Type	Rack-mount, Cabinet-mount
Application	Data Centre, Enterprise Networks
Brand	EDGE™

Standards	
RoHS	Free of hazardous substances according to RoHS 2011/65/EU

Design	
Lockable	Yes
Number of modules	48
Cable entry type	Side brush entry



Design	
Number of Panels/Cassettes per Housing	48
Cable Entry Direction	Rear
Housing type	EDGE™
Colour	Silver
Panel or cassette type	EDGE™
Panel or module type	EDGE™
Fibre Capacity	576

Design - Adapter	
Adapter housing colour	Silver

Dimensions	
Height	177 mm
Width	432 mm
Depth	561 mm
Weight	14.5 kg

Ordering Information	
Product Number	EDGE-04U-GND
Package contents	EDGE™ Housing 4U; Quick Start Guide, #12-24 and #10-32 mounting screws, Cage Nut Mounting Kit, Velcro Strap, Fiber Optic Warning Label
Shipping weight	16.8 kg
Module Capacity	48
Height Unit	4 U
Units per delivery	1/1
Trunk Capacity	48 (size 1 or 2, double stack cradle)
Shipping Height	305 mm



Ordering Information	
Shipping Width	565 mm
Shipping Depth	660 mm



Corning Optical Communications GmbH & Co. KG • Leipziger Strasse 121 • 10117 Berlin, Germany +00 800 2675 4641 • FAX: • www.corning.com/opcomm/emea

A complete listing of the trademarks of Corning Optical Communications is available at www.corning.com/opcomm/emea/trademarks. Corning Optical Communications is ISO 9001 and ISO 14001 certified. © 2025 Corning Optical Communications. All rights reserved.