

EDGE™ 2.0mm Patch Cord, 2 fibres, Interconnect tight-buffered cable LSZH, SMF-28® Ultra Single-mode OS2, Low-Loss, LC Uniboot - LC Uniboot, 2.5 m



Part Number:
E787802GNZ20002.5M

EDGE™ patch cords are integrated reverse-polarity uniboot duplex assemblies that meet the high-density space requirements of the MDA and EDA and provide a 50-percent reduction in bulk cabling when compared to traditional duplex patch cords. The highly flexible, 2-fiber interconnect cable reduces cable congestion, improves patch cord management and routing and improves air circulation.

Features and Benefits

State-Of-The-Art Manufacturing Processes

Corning proprietary manufacturing processes and advanced technology result in unsurpassed product consistency

Global operations


Worldwide manufacturing facilities and end-to-end vertical integration across the entire process ensure reliable supply and mitigate trade barriers or supply disruptions

Flexible design options

Choice of materials for strength elements and fibre properties dependent on application requirements

Superior Performance Testing

Every termination is tested to ensure the highest in network performance



EDGE™ 2.0mm Patch Cord, 2 fibres, Interconnect tight-buffered cable LSZH, SMF-28® Ultra Single-mode OS2, Low-Loss, LC Uniboot - LC Uniboot, 2.5 m



Specifications

General Specifications	
Flame rating	LSZH/FRNC
Fibre category	Bend-improved Single-Mode (OS2)
Product category	Core product / Fastship
Cable assembly type	Two fibre
Cable Type	Tight-buffered

Standards	
RoHS	Free of hazardous substances according to RoHS 2011/65/EU

Environmental Conditions	
Temperature range, installation	-5 °C to 50 °C
Temperature range, operation	-10 °C to 60 °C
Temperature range, storage	-10 °C to 60 °C

Design	
Fibre count	2
Outer jacket material	LSZH/FRNC
Outer jacket colour	Yellow

Mechanical Characteristics	
Fire load	0.3 MJ/m
Minimum bend radius	10 mm
Tensile strength	150 N
Crush resistance	1000 N/10 cm

EDGE™ 2.0mm Patch Cord, 2 fibres, Interconnect tight-buffered cable LSZH, SMF-28® Ultra Single-mode OS2, Low-Loss, LC Uniboot - LC Uniboot, 2,5 m



Optical Characteristics	
Cable cutoff wavelength	1260 nm
Fibre code	Z
Fibre name	SMF-28® Ultra TB Cable Optical Fibre
Fibre Type	Single-mode
Fibre compliance	ITU-T G.652.D and ITU-T G.657.A1
Cladding diameter	125 µm
Maximum Attenuation	0.38 dB/km / 0.38 dB/km / 0.25 dB/km
Mode-Field Diameter at 1310 nm	9.2 µm
Serial 1 gigabit ethernet	5000 MHz*km / - / -
Serial 10 gigabit ethernet	10000 MHz*km / 40000 MHz*km
Wavelengths	1310 nm / 1383 nm / 1550 nm
PMD Link Design Value	≤ 0.04 ps/(nm*km)
PMD (Polarization Mode Dispersion) maximum individual fibre	≤ 0.1 ps/(nm*km)
Coating diameter	242 µm

Specifications - Connector A	
Reflectance, typical	≤ -58 dB
Polish	UPC
Insertion loss, typical	0.1 dB
Insertion loss, max.	0.15 dB
Tensile strength jacketed cable	44 N
Durability	≤ 0.2 dB change, 500 rematings, FOTP-21
Keyed (security)	No
Boot colour	Blue
Connector type	LC Uniboot
Ferrule material	Ceramic
Housing colour	Blue
Housing material	Composite
Boot type	Uniboot

EDGE™ 2.0mm Patch Cord, 2 fibres, Interconnect tight-buffered cable LSZH, SMF-28® Ultra Single-mode OS2, Low-Loss, LC Uniboot - LC Uniboot, 2.5 m



Specifications - Connector B	
Reflectance, typical	≤ -58 dB
Polish	UPC
Insertion loss, typical	0.1 dB
Insertion loss, max.	0.15 dB
Tensile strength jacketed cable	44 N
Durability	≤ 0.2 dB change, 500 rematings, FOTP-21
Keyed (security)	No
Boot colour	Blue
Connector type	LC Uniboot
Ferrule material	Ceramic
Housing colour	Blue
Boot type	Uniboot

Dimensions	
Length	2.5 m
Outer diameter	2 mm
Weight	0.02 kg

Ordering Information	
Product Number	E787802GNZ20002.5M
EAN Code	4042673326571
Packaging method	Cardboard box
Units per delivery	1/1
Shipping Height	180 mm
Shipping Width	250 mm
Shipping Depth	380 mm

EDGE™ 2.0mm Patch Cord, 2 fibres, Interconnect tight-buffered cable LSZH, SMF-28® Ultra Single-mode OS2, Low-Loss, LC Uniboot - LC Uniboot, 2.5 m

CORNING



Corning Optical Communications GmbH & Co. KG • Leipziger Strasse 121 • 10117 Berlin, Germany
+00 800 2675 4641 • FAX: • www.corning.com/opcomm/emea

A complete listing of the trademarks of Corning Optical Communications is available at www.corning.com/opcomm/emea/trademarks. Corning Optical Communications is ISO 9001 and ISO 14001 certified. © 2025 Corning Optical Communications. All rights reserved.