

# EDGE8™ Housing

2 U, holds up to 36 EDGE8 modules or adapter panels

CORNING

EDGE8™ solutions are high-density preterminated optical cabling solutions with optimised design for Base-8 fibre applications offering industry-leading connector density. With sufficient connector finger access, there is no need for additional tools enabling faster moves, adds, and changes (MACs).

## Features and Benefits

### Smaller footprint design with Base-8 components in housings

Greater flexibility with six open slots per tray, for easy deployment of EDGE8™ modules and panels

### Key identifiers

EDGE8 printed on housing for easy identification as a Base-8 component

### Sliding drawer-style hardware with integrated cable routing guides and port identification

Optimised finger access to connectors combined with industry leading port density

### Integrated strain-relief plate can rotate 90°

Allows for rear cable entry direction, as well as the traditional side cable entry

### Removable top covers on the 1U and 2U housings

Provides easier access to modules and panels

### Quick mounting system

Enables one-person installation and depth adjustment of the housing in the rack

### Ultra high port concentration with MTP Base-8 system in 2 U housing

144 LC duplex ports (288 fibre) or 144 MTP ports (1152 fibre)



Part Number: EDGE8-02U



Part Number: EDGE8-02U

# EDGE8™ Housing

2 U, holds up to 36 EDGE8 modules or adapter panels



## Specifications

General Specifications	
Application	Data Centre
Product type	Fibre Optic Hardware
Mounting type	Rack 19"

Design - Hardware	
Height Unit	2U
Housing Colour	Silver
Housing type	EDGE™
Number of Panels per Housing	36

Mechanical Characteristics	
Dimensions (W x D x H)	432 mm x 561 mm x 88 mm (17.0 in x 22.1 in x 3.5 in)

Chemical Characteristics	
RoHS	Free of hazardous substances according to RoHS 2011/65/EU

## Ordering Information

Part Number	EDGE8-02U
Product Description	EDGE8™ Housing, 2 U, holds up to 36 EDGE8 modules or adapter panels
EAN Code	4056418139692

## Shipping Information

Units Per Delivery	1/1
Packaging Dimensions (W x D x H)	578 mm x 667 mm x 241 mm (22.75 in x 26.25 in x 9.5 in)
Shipping Weight	10.4 kg (23 lb)

# EDGE8™ Housing

2 U, holds up to 36 EDGE8 modules or adapter panels

The CORNING logo is a blue square with the word "CORNING" in white, uppercase, sans-serif font centered inside.

## Notes



**Corning Optical Communications GmbH & Co. KG · Leipziger Strasse 121 · 10117 Berlin, GERMANY  
00 800 2676 4641 · FAX: +49 30 5303 2335 · [www.corning.com/opcomm/emea](http://www.corning.com/opcomm/emea)**

A complete listing of the trademarks of Corning Optical Communications is available at [www.corning.com/opcomm/emea/trademarks](http://www.corning.com/opcomm/emea/trademarks). Corning Optical Communications is ISO 9001 and ISO 14001 certified. © 2016 Corning Optical Communications. All rights reserved.