

## Rip-Tie Lite and WrapStrap Product Specifications



This is a reusable hook and loop material most commonly used for dressing cables and is recommended as a replacement for plastic wire ties. These specifications apply to our Y, X, and W series part numbers.

**Materials:** Nylon Loop / Polyethylene hook

**Cycles:** 200-300

**Average Shear Value:** 23 PSI

**Average Peel Value:** 0.5 PIW

**Operating Temperature Range:** 0 - °220° F

**Thickness:** 0.05 in.

**Colors:** Black, White, Beige, Gray, Royal Blue, Red, Coachman Green, Yellow, Orange, Brown, Purple

**Available Widths of Wrapstrap :** 3/8", 1/2", 5/8", 3/4" 1", 1 1/2", 2", 4"

**Rip-Tie Lite CableWrap:** Head width is 3/4", tail width is 1/2". Refer to a Rip-Tie price list for part numbers, packaging and available lengths.

### Rip-Tie Lite / Wrapstrap Fire Retardant

These are the F and G series parts (not including RipWrap).

### Product Specifications

**Materials:** Nylon Loop / Polypropylene hook

**Cycles:** 50

**Average Shear Value:** 29 PSI

**Average Peel Value:** 0.6 PIW

**Operating Temperature Range:** Max 122° F

**Rated Load:** 18 Lbs.

**Colors:** Black and Cranberry

**Minimum Contact area:** 0.75 Square Inches

**Available widths of FR WrapStrap :** 1/4", 3/8", 1/2", 5/8", 3/4", 1" – see price list for available roll lengths.

**FR Lite CableWrap:** Head width is 3/4". Tail width is 1/2". See Rip-Tie price list for part numbers, packaging and available lengths

**This product meets the requirements of the following rating:**

UL 94-V2

FAR 25.853 Appendix F (a) (1) 60 second burn and 12 second burn,  
NEC 300-22 (C) & (D)

This product meets acceptance as a Wire Positioning Device (16SA) in air handling spaces, in accordance with Section 300-22 paragraph (c) and (d) of the National Electrical Code. This allows RTL FR to be used for wire or cable management above a hung ceiling or below a raised floor.

Meets UL 2043 regulations.

**Both of these products meet ROHS requirements and are Made in the USA.**

P O Box 549  
San Leandro  
California 94577

tel: (510) 577-0200  
fax: (510) 553-0160  
www.riptie.com  
info@riptie.com

